



Built for Life.

Build a Shelter: Freedom Series™

Fax Completed Form to (314) 664-9301
Or E-mail to Sales@ShelterWorks.com

Contact & Project Information

Office Use: Today's Date: ___/___/___ Initials: _____

Name:		Project Name:	
Title:		Submittal Drawings <input type="checkbox"/> Y <input type="checkbox"/> N Engineer Stamp <input type="checkbox"/> Y <input type="checkbox"/> N	
Company:		3 rd Party State Certification <input type="checkbox"/> Y <input type="checkbox"/> N Calculations <input type="checkbox"/> Y <input type="checkbox"/> N	
Street:		Purchasing Time Frame: <input type="checkbox"/> Now <input type="checkbox"/> 3-6 mos <input type="checkbox"/> >6mos	
City:	State:	Zip:	
Phone:	Cell phone:	Fax:	
E-mail:	Website:	Bid Date:	
Ship To City, State & Zip:		Delivery Date Needed:	
How Did You Hear About Us?			

Standard Features List with Design Criteria

- Wall Height: 6, 8, or 10 feet
- Width: 4 feet to 16 feet in 2 feet increments
- Length: Up to 40 feet in 2 feet increments
- Insulation: 1 ½ inch foam core (Wall Thickness 1.75")
- Hip Roof with 1 ½ inch foam core insulation
- Door: One 3' x 6'8" single door w/ 3-point zinc latch
- Snow load – 30 p.s.f.
- Wind Load – 100 mph
- R-10 Insulation Value
- White interior & exterior gel coat
- 4.75" base flange
- FiberBeam™ Technology

Choose Options, Enhancements, Supplements

Shelter Structure	Doors/Hardware	Electrical/Lighting	HVAC
Color <input type="checkbox"/> Polar White <input type="checkbox"/> Desert Sand <input type="checkbox"/> Storm Grey <input type="checkbox"/> Meadow Green <input type="checkbox"/> Other	Doors (Fiberglass) <input type="checkbox"/> 3'-0" x 6'-8" single door <input type="checkbox"/> 6'-0" x 6'-8" double door <input type="checkbox"/> 8'-0" x 6'-8" double door <input type="checkbox"/> 4'-0" x 4'-0" single door With window? <input type="checkbox"/> Yes <input type="checkbox"/> No	Electrical Classification Nema Rating _____ <input type="checkbox"/> Non-Hazardous <input type="checkbox"/> Hazardous	Air Conditioner <input type="checkbox"/> Through Wall <input type="checkbox"/> Wall Pack _____ Phase _____ Voltage <input type="checkbox"/> Combination with Heat Size Cool: _____ ton(s) Size Heat: _____ KW
Size _____ ft x _____ ft x _____ ft length x width x height (OD) (OD) (ID)	Lock Type Hardware <input type="checkbox"/> 3-point latch w/ override (zinc) <input type="checkbox"/> 3-point latch (stainless) <input type="checkbox"/> 2-point latch (zinc) <input type="checkbox"/> Panic <input type="checkbox"/> Panic (stainless) <input type="checkbox"/> Cylindrical	Breaker Panel(s) <input type="checkbox"/> Yes _____ Amp _____ Voltage _____ Phase _____ # of Breakers <input type="checkbox"/> No	Heaters <input type="checkbox"/> Gas <input type="checkbox"/> Propane Size BTU/hr: _____ <input type="checkbox"/> Electric KW _____ Phase _____ Voltage _____ <input type="checkbox"/> Bracket <input type="checkbox"/> Baseboard Quantity _____
R Value Roof _____ Walls _____	Threshold <input type="checkbox"/> Standard (2.5 inch) <input type="checkbox"/> Trip-Proof <input type="checkbox"/> Elevated _____ Inches	Transformer(s) <input type="checkbox"/> Yes <input type="checkbox"/> No	Natural Ventilation <input type="checkbox"/> 12" through roof turbine vent <input type="checkbox"/> Through Wall Vent <input type="checkbox"/> 8 inch <input type="checkbox"/> 12 inch <input type="checkbox"/> Other
Plywood Reinforced Walls <input type="checkbox"/> Yes <input type="checkbox"/> Partial Wall <input type="checkbox"/> 1-Wall <input type="checkbox"/> All Walls <input type="checkbox"/> No	Garage Doors <input type="checkbox"/> Roll Up <input type="checkbox"/> Sectional <input type="checkbox"/> Insulation	Conduit <input type="checkbox"/> EMT <input type="checkbox"/> PVC <input type="checkbox"/> PVC Coated RGS <input type="checkbox"/> Liquid Tight PVC <input type="checkbox"/> Rigid Explosion Proof	Exhaust Shutter Fans CubicFt/Minute _____ <input type="checkbox"/> Corrosion-Resistant <input type="checkbox"/> Switch <input type="checkbox"/> Limit <input type="checkbox"/> Wall <input type="checkbox"/> Thermostat Quantity _____
Floor System <input type="checkbox"/> Yes <input type="checkbox"/> Steel <input type="checkbox"/> Aluminum <input type="checkbox"/> Composite <input type="checkbox"/> Containment Loading (P/SF) _____ <input type="checkbox"/> No	Windows & Skylights <input type="checkbox"/> 15" x 15" vinyl window <input type="checkbox"/> 36" x 36" vinyl window <input type="checkbox"/> Screen <input type="checkbox"/> Translucent Skylights Width _____ Length _____ <input type="checkbox"/> Other	Interior Lights <input type="checkbox"/> Fluorescent Quantity _____ <input type="checkbox"/> Incandescent Quantity _____ Wattage _____ <input type="checkbox"/> Switch <input type="checkbox"/> Limit <input type="checkbox"/> Wall	Intake Louvers Quantity _____ Construction Material: <input type="checkbox"/> Fiberglass <input type="checkbox"/> Aluminum <input type="checkbox"/> Galvanized Actuation: <input type="checkbox"/> Thermal (Aluminum Only) <input type="checkbox"/> Gravity <input type="checkbox"/> Motorized
Placement On Site <input type="checkbox"/> Concrete Slab Mounted <input type="checkbox"/> Anchors needed Base Gasket for Installation <input type="checkbox"/> Butyl Tape <input type="checkbox"/> Neoprene Tape	Exterior Lights <input type="checkbox"/> 70 watt HPS Wall Pack w/ photo cell <input type="checkbox"/> Incandescent with a switch <input type="checkbox"/> Other <input type="checkbox"/> None	Special Lighting <input type="checkbox"/> Dual Volt Emergency <input type="checkbox"/> Red Strobe <input type="checkbox"/> Other Comments: _____	Convenience Receptacles _____ Quantity <input type="checkbox"/> 15 Amp <input type="checkbox"/> 20 Amp <input type="checkbox"/> GFI
Custom <input type="checkbox"/> Partition Walls <input type="checkbox"/> Custom Formed Openings # of Openings: _____ Size of Openings: _____ <input type="checkbox"/> Knock-out Panels # of Panels: _____ Size of Panels _____			

Please contact me regarding additional specifications not highlighted on this short form. Comments: